

RACKET STREETLIGHT®

Vägbelysningsarmaturer i aluminium med toppkvalitet, Välj mellan 110 eller 160lm/W. Den rektangulära ljusbilden sprider ljuset perfekt utefter vägen. Med Mean Well driver.



ARTIKELNUMMER	BESKRIVNING	DIODER
RSL30-(30-60)	Racket Street Light® 30W, 110lm/W	1X30W COB
RSL40-(30-60)	Racket Street Light® 40W, 110lm/W	1X40W COB
RSL50-(30-60)	Racket Street Light® 50W, 110lm/W	1X50W COB
RSL60-(30-60)	Racket Street Light® 60W, 110lm/W	1X60W COB
RSL70-(30-60)	Racket Street Light® 70W, 110lm/W	1X70W COB
RSL80-(30-60)	Racket Street Light® 80W, 110lm/W	1X80W COB
RSL90-(30-60)	Racket Street Light® 90W, 110lm/W	2X45W COB
RSL100-(30-60)	Racket Street Light® 100W, 110lm/W	2X50W COB

ARTIKELNUMMER	BESKRIVNING	DIODER
RSL31-(30-60)	Racket Street Light® 30W, 160lm/W	1X70W COB
RSL41-(30-60)	Racket Street Light® 40W, 160lm/W	1X90W COB
RSL51-(30-60)	Racket Street Light® 50W, 160lm/W	2X60W COB
RSL61-(30-60)	Racket Street Light® 60W, 160lm/W	2X70W COB
RSL71-(30-60)	Racket Street Light® 70W, 160lm/W	2X80W COB
RSL81-(30-60)	Racket Street Light® 80W, 160lm/W	2X90W COB
RSL91-(30-60)	Racket Street Light® 90W, 160lm/W	3X70W COB
RSL101-(30-60)	Racket Street Light® 100W, 160lm/W	3X80W COB

INFO

- 30-100W
- Ljusflöde: 110/160lm/W
- Färgtemperatur: 3000-6000K
- 5 års produktgaranti
- CRI / RA: >80
- IP65
- CE, RoHs